

TECHNICAL SPECIFICATION

Product Specification For: SCAFFOLDING SUPPLIES LIMITED

**Scope of Specification: 38x225 Whitewood Scaffold Boards
Graded to BS2482:2009
1.5m Support Centre – 3.9m, 3.0m & 2.4m
Banded & Branded
Fire Retardant Treated to Burnblock Euroclass B
PEFC Certified Material (BMT-PEFC-1596)**

Fixing Requirements

All fixings are to be galvanised or zinc coated to prevent rusting.

End Band - MACHINE GRADED boards – 2 END BANDS per board

SUPPORT EVERY 1.5M MAX	 <p style="text-align: center; color: red; font-weight: bold;">PLAIN</p>	BS 2482/09 KM 564923		MG
---------------------------	--	-------------------------	---	----

Branding – 2.4m, 3.0m, 3.9m - 2 brands per side as per detail below

Side 1



Side 2



Packaging Requirements

Boards packed as standard in 100 pieces per pack – 20 boards' high x 5 boards wide.
Packs to be strapped in 2 places, approx. 0.5m from each end - additional pack straps will be added if required to maintain stability for transportation purposes.

Dimensions

Boards to be within +/- 25mm in length.
Board thickness to be 38mm +/- 2mm.
Board width to be 225mm +/- 5mm.

Pack / Timber Appearance

Pack to be square stacked.
Pack to be free from ground splash.
Boards must be 'rot-free', i.e. no dark damp patches in a dry board.
Sap stain acceptable.